

Legend 880/Tasword II Instructions

Copyright 1985 by E. Arthur Brown Company

















To set up your Legend 880 for Tasword II Word Processing, first remember that Tasword II has the printer driver software already in it, so you mustn't load the Tasman Centronics Interface software tape. Before powering up, be sure your Tasman interface is firmly connected to your computer and it's cable is firmly connected to your Legend 880. Power up everything and load Tasword II by typing LOAD "" (ENTER) and pressing the PLAY button of your recorder. Once the program is loaded, hold down the symbol shift key and press STOP. A menu will appear. Press the "g" selection and (ENTER). You will be presented with a display that's similar, but different from the one below. Change it to match the one below and you will configure Tasword II to use the special features of your Legend 880 printer.

Tasword Two-2068 Microdrive
© Tasman Software 1983
Printer control graphics chars:

128		7	0	0	
130	129	7	0	0	
132	131	7	4	0	
134	133	7	7	0	
136	135	7	4	2	7
138	137	7	4	1	7
140	139	7	5	0	
142	141	5	4	1	
143		7	8	1	

↑ CODE CHANGES

MENU CHANGES

On	Legend 880	Off	Key
	Enlarged		1
	Condensed		2
	Underlined		3
	Italic		4
	Emphasized		5
	Superscript		6
	Subscript		7
	Form Feed		8

Next, use the instructions from your Tasword II tip sheet to modify the help menu to show the changes in functions you've made so you'll have those references on screen when using Tasword II.

Finally, a tip for using the Tasman Centronics Interface for making High Resolution Screen copies with your Legend 880: LOAD "tas-shinwa" CODE for the interface. The command RANDOMIZE USR 23296 will give a screen copy the full width of your paper. If you want a small screen copy, use the command POKE 23548,1 before using the RANDOMIZE USR 23296 command. Incidentally, the tas-shinwa program is on the interface tape.